

LAW OFFICES
SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC
2100 PENNSYLVANIA AVENUE, N.W.
WASHINGTON, DC 20037-3213
TELEPHONE (202) 293-7060
FACSIMILE (202) 293-7860
www.sughrue.com

December 13, 2000

BOX PCT

Assistant Commissioner for Patents
Washington, D.C. 20231

PCT/FR00/00958
-filed April 13, 2000

Re: Application of Hikmet SARI
METHOD FOR REDUCING INTERFERENCE BETWEEN USERS AND USE
THEREOF IN A RADIO ACCESS NETWORK
Our Ref: Q62241

Dear Sir:

The following documents and fees are submitted herewith in connection with the above application for the purpose of entering the National stage under 35 U.S.C. § 371 and in accordance with Chapter I of the Patent Cooperation Treaty:

- ☒ an executed Declaration and Power of Attorney.
- ☒ an English translation of the International Application.
- ☒ 4 sheets of formal drawings.
- ☐ an English translation of Article 19 claim amendments.
- ☐ an English translation of Article 34 amendments (annexes to the IPR).
- ☒ an executed Assignment and PTO 1595 form.
- ☒ an Information Disclosure Statement with Form PTO-1449 listing the ISR references, and a complete copy of each reference.
- ☒ a Preliminary Amendment

It is assumed that copies of the International Application, the International Search Report, the International Preliminary Examination Report, and any Articles 19 and 34 amendments as required by § 371(c) will be supplied directly by the International Bureau, but if further copies are needed, the undersigned can easily provide them upon request.

SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC

Assistant Commissioner of Patents
Washington, D.C. 20231

Page 2

Attorney Docket Q62241

December 13, 2000

**PLEASE SEE THE ATTACHED PRELIMINARY AMENDMENT BEFORE
CALCULATING THE FEE**

The Government filing fee is calculated as follows:


Total claims	<u>9</u>	-	20	=	<u> </u>	x \$18.00 =	<u>\$0.00</u>
Independent claims	<u>1</u>	-	3	=	<u> </u>	x \$80.00 =	<u>\$0.00</u>
Base Fee							\$860.00

TOTAL FILING FEE	<u>\$860.00</u>
Recordation of Assignment	<u>\$ 40.00</u>
TOTAL FEE	\$900.00

Checks for the statutory filing fee of \$860.00 and Assignment recordation fee of \$40.00 are attached. You are also directed and authorized to charge or credit any difference or overpayment to Deposit Account No. 19-4880. The Commissioner is hereby authorized to charge any fees under 37 C.F.R. §§ 1.16, 1.17 and 1.492 which may be required during the entire pendency of the application to Deposit Account No. 19-4880. A duplicate copy of this transmittal letter is attached.

Priority is claimed from April 15, 1999 based on French Application No. 9904754.

Respectfully submitted,


David J. Cushing
Registration No. 28,703

SUGHRUE, MION, ZINN,
MACPEAK & SEAS, PLLC
2100 Pennsylvania Avenue, N.W.
Washington, D.C. 20037-3213
Telephone: (202) 293-7060
Facsimile: (202) 293-7860

Date: December 13, 2000

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of PCT/FR00/00958
Hikmet SARI Attorney Docket Q62241
Appln. No.: Group Art Unit:
Filed: December 13, 2000 Examiner:
For: METHOD FOR REDUCING INTERFERENCE BETWEEN USERS AND USE
THEREOF IN A RADIO ACCESS NETWORK

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Prior to examination, please amend the above-identified application as follows:

IN THE SPECIFICATION:

Page 1, after the title, insert the heading --Background of the Invention--.

Page 4, after line 10, insert the heading --Summary of the Invention--.

Page 6, after line 13, insert the heading --Brief Description of the Drawings--.

after line 36, insert the heading --Detailed Description of the Invention--.

IN THE CLAIMS:

Claim 4, line 1, delete "any one of claims 1 to 3" and insert -- claim 1--.

Claim 5, line 1, delete "any one of claims 1 to 4" and insert --claim 1--.

Claim 6, line 1, delete "any one of claims 1 to 5" and insert --claim 1--.

Claim 7, line 1, delete "any one of claims 1 to 6" and insert --claim 1--.

Claim 8, line 1, delete "any one of claims 1 to 7" and insert --claim 1--.

AMENDMENT
Attorney Docket Q62241

Claim 9, line 1, delete "any one of claims 1 to 8" and insert --claim 1--.


IN THE ABSTRACT:

After the heading "Abstract" delete the title.

REMARKS

Entry and consideration of this Amendment is respectfully requested.

Respectfully submitted,



David J. Cushing
Registration No. 28,703

SUGHRUE, MION, ZINN,
MACPEAK & SEAS, PLLC
2100 Pennsylvania Avenue, N.W.
Washington, D.C. 20037-3213
Telephone: (202) 293-7060
Facsimile: (202) 293-7860

Date: December 13, 2000

4/PRTS

A METHOD OF REDUCING INTERFERENCE BETWEEN USERS AND USE
OF THE METHOD IN A RADIO ACCESS NETWORK

The present invention relates to a method of
reducing interference between users and to use of the
method in a radio access network. The preferred field of
the invention is that of radio access networks using
millimeter or sub-millimeter frequencies, referred to in
the literature as local multipoint distribution systems
(LMDS), for example. In LMDS networks, a base
transceiver station uses a sectorial antenna and the
antenna of the terminal of a user is a directional
antenna pointed towards the base transceiver station
serving a cell in which the terminal is located. The
antenna of the base transceiver station need not be a
sectorial antenna, however. The above systems are
described in the article "Broadband radio access to home
and businesses: MMDS and LMDS" by Hikmet SARI, published
in the journal Computer Networks, Vol.31, by Elsevier
Science Holland in 1999, pages 379 to 393.

The above networks provide an alternative to
existing cable networks (copper wire pairs, coaxial
cables or optical fibers), which have performance
limitations or unacceptable infrastructure costs. The
object of the invention is to solve interference problems
which occur in the above networks.

In multipoint radio access networks, the base
transceiver station antenna can be an omnidirectional
antenna or a sectorial antenna. In the case of a
sectorial antenna, a cell of the network comprises a
plurality of sectors. Each sector conventionally uses a
different frequency to the other sectors of the same cell
(each sector can use a subset of frequencies and the
subsets used in different sectors can be disjoint). The
object of the principle adopted for allocating
frequencies between adjoining cells is to minimize
potential interference generated within the cellular
network.

Figure 1 shows an example of a rectangular LMDS network with 90° sectors. Four frequencies or subsets of frequencies 1, 2, 3 and 4 are used in this type of cellular network, in which each cell is square and has a base transceiver station at its center. The base transceiver stations are represented by circles. Each cell is divided into four sectors corresponding to the four sectorial antennas of the base transceiver station. The continuous lines in Figure 1 are the boundaries between the sectors of the same cell. The dashed lines are the boundaries between the cells. Fixed user terminals are represented by dots. For example, the dots A, B and C represent terminals located in the same sector of the same cell.

One of the cells is shaded in the diagram. Each of the four sectors in a cell is labeled by a digit which indicates the frequency or the set of frequencies assigned to it. It can be seen that all the base transceiver stations use the same frequencies but that the frequencies are assigned to the various cells of the network in such a way that there is no interference between adjacent cells.

Other cellular network geometries can be defined, using sectorial antennas with different angular subdivisions, for example: 120° , 60° , or 45° . In all cases, operation of the network entails using a plurality of frequencies for each cell and generates interference between users of the system.

The carrier to interference (C/I) ratio is a function of the position of the user. The worst case scenario corresponds to points at the ends of the horizontal, vertical and diagonal lines of the cells for each base transceiver station. An antenna associated with the terminals located at these points is directed not only in the direction of its own base transceiver station but also in the direction of base transceiver stations on the same horizontal (or vertical or diagonal)

line. Given the way the frequencies are assigned, there is interference with a base transceiver station immediately following an adjacent base transceiver station along the horizontal (or vertical or diagonal) line. However, there is no interference with the adjacent base transceiver station.

Unfortunately, the ratio between the respective path lengths carrying a payload signal and an interference signal is small. For example, for the sector 1 of the base transceiver station in the top left-hand part of Figure 1, the three points A, B and C are the three least favorable points. If the distance between two adjoining base transceiver stations is denoted $2D$, users at points B and C at the edge of the cell (and therefore at a distance D from their base transceiver station) with their terminal pointed towards their base transceiver station interfere with the base transceiver station at a distance $5D$ ($D+2D+2D$). The terminal B shown in Figure 2 is at the limit of the cell, on a horizontal straight line segment joining the base transceiver stations of the network. Of course, the same schematic could be applied at point C, on a vertical line joining the base transceiver stations. In the diagonal case (at point A), a factor $\sqrt{2}$ is applied to all the distances and the end result is the same.

Assuming that all the base transceiver stations transmit at the same power, the carrier/interference ratio is $C/I = 10\log(5^2)$, i.e. 14 dB. This description corresponds to a time division multiple access (TDMA) system having four frequency channels to cover the whole of a geographical area. If there are only two channels available, the C/I ratio associated with the least favorable points is then $C/I = 10\log(3^2)$, i.e. 9.5 dB. This can readily be shown by replacing 4 with 2 and 3 with 1 in Figures 1 and 2. It is then clear that in this case there is interference between adjacent cells.

The frequency allocation architecture chosen is

decisive in this regard. An operator is allocated a frequency band, which is by definition limited, in a given frequency range. This band has to carry uplink calls and downlink calls for each sector, allowing for the fact that the base transceiver station transmits omnidirectionally, or at least sectorially, and the terminals transmit directionally. Considerations of equipment economy in the base transceiver stations lead to the choice of omnidirectional transmission for a base transceiver station.

An object of the invention is to remedy the above drawbacks and to provide an access technique in which such interference is no longer a problem. Although the invention is directed to solving problems encountered on the downlink, there is nothing to prevent it being used also for the uplink. The invention therefore teaches, for the downlink at least, using a CDMA spread spectrum coding method employing the same frequency in all sectors. With CDMA spread spectrum coding, transmitted +1 and -1 binary symbols are coded by multiplying them by a sequence of +1 and -1 coding bits, the sequence comprising $2N$ bits. The result of such multiplication is a sequence of +1 and -1 binary signals referred to as chips, the sequence comprising $2N$ chips. The chips are then used to modulate a carrier whose signal is radiated by the antenna of the base transceiver station. Because the time allocated for sending a symbol remains the same, other things being equal, the spectrum spreading factor resulting from this process is $2N$. With orthogonal coding sequences, for example Walsh Hadamard (WH) sequences, the number of different sequences that can be used is $2N$. The number of users that can be accommodated simultaneously in this geographical situation is therefore $2N$ per cell if the radiation is omnidirectional and if a sequence is associated with each user.

In the access networks with directional user antennas described above, one type of interference to be

countered is entirely geometrical. It primarily affects terminals receiving transmissions from base transceiver stations aligned with them. For example, a receiver at point B in Figure 2 receives transmissions from base transceiver stations BTS1 and BTS2 because it points towards the base transceiver station BTS1. Because all the base transceiver stations transmit the same carrier, an interference problem arises at point B. Because the base transceiver stations are not synchronized, the orthogonal coding by coding sequences $2N_i$ (the coding sequence $2N_i$ is allocated to the downlink call from BTS1 to B) in no way protects the receiver B from transmissions from stations BTS2 and BTS3.

In accordance with the invention, to transmit a message to the user B from the base transceiver station BTS1, each symbol is coded with a double WH sequence. The double sequence includes first and second single sequences. In the remainder of this description, the term "single" sequence of length $2N$, is used for a sequence that is useable in the conventional way with a spectrum spreading factor $2N$, and the term "double" sequence of length $4N$ (or "triple" sequence of length $6N$, or "quadruple" sequence of length $8N$, etc.), is used for a sequence that is suitable for use in the invention, likewise with a spectrum spreading factor $2N$. A solution of the above kind effectively solves the problem because the user B will receive the transmissions addressed to them from the base transceiver station BTS1 with a sequence $2N_i 2N_i$. The sequence $2N_i 2N_i$ is in this case a double sequence of length $4N$. Received chips coded with the expected double sequence $2N_i 2N_i$ will be decoded at a level 3 dB greater than chips coded with a single $2N_i$ sequence. This improves the quality of the received payload signal by 3 dB. In some cases this is sufficient for the payload signal to be recognized. If necessary, a symbol can be coded for transmission by a triple sequence, a quadruple sequence or any multiple sequence.

This progressively improves the signal to noise ratio.

The invention therefore provides a method of transmitting CDMA messages between a base transceiver station and user terminals, wherein:

5 - symbols of messages to certain user terminals are coded with a coding sequence of $2N$ bits to produce sequences of $2N$ chips, and

 - the chips are transmitted,
 characterized in that:

10 - symbols of other messages to certain other user terminals are coded with a coding sequence of $k2N$ bits to produce sequences of $k2N$ chips, where k is an integer greater than 1.

15 The invention will be better understood on reading the following description and examining the accompanying drawings. The drawings are provided only by way of non-limiting and illustrative example of the invention. In the figures:

20 Figure 1 shows a rectangular cellular network with 90° sectors and has already been commented on;

 Figure 2 shows an interference scenario in the network shown in Figure 1 and has already been commented on;

25 Figure 3 shows the assignment in accordance with the invention of orthogonal CDMA coding sequences within a cell;

 Figure 4 shows a preferred way to generate a CDMA coded signal;

30 Figure 5 shows interference on an uplink channel from a user to a base transceiver station;

 Figure 6 shows interference on a downlink channel from a base transceiver station to a user;

 Figure 7 shows areas subject to high interference (in the downlink direction) shaded; and

35 Figures 8a and 8b show different coding modes in accordance with the invention.

 The networks described above show the limitations of

TDMA cellular networks. For a network with four frequency bands (occupied band 4W), in the worse case scenario, the carrier to interference (C/I) ratio is 14 dB. For a network with two frequency bands (occupied band 2W) the C/I ratio is 9.5 dB. The invention proposes to use a different access technology to improve these limitations, for example to obtain a C/I ratio better than 9.5 dB for an occupied band 2W. To this end, in accordance with the invention, the same frequency can be used in all sectors by employing the CDMA technique. A variant of that technique is proposed which significantly increases the C/I ratio associated with the least favorable positions.

As previously, an example is described which concerns a cellular network whose geometry reproduces that shown in Figure 1, but in which the four carrier frequencies (or groups of frequencies) 1 to 4 are replaced with a common carrier frequency coded by disjoint subsets S1 and S2 of orthogonal decoding sequences (for example Walsh-Hadamard sequences) of length 2N. Figure 3 shows this. If there are more than four sectors, for example six or eight sectors, disjoint subsets of orthogonal sequences are allocated to two adjacent sectors in the cell. The number 2N is adopted here to simplify comparing the carrier to interference ratio of the invention to that of the prior art. However, this is not obligatory. The number could even be odd, although it is preferably even for other reasons.

The subsets S1 and S2 are assigned to the four sectors of a cell as follows. Two sectors of a cell on a diagonal line are served by a common subset of sequences S1 (or S2). Two contiguous sectors, meaning sectors which are side-by-side but in two adjacent cells, are served by two identical subsets S1 (or S2) of sequences. To achieve symmetry, the number of sequences in each subset will be N. This is not obligatory, however. If necessary, the general sequence distribution plan could

be altered. This mode of assigning frequencies prevents interference between neighboring sectors in a cell because of the orthogonal relationship of any of the sequences in subsets S1 and S2.

5 All the cells of the network and all the sectors of each cell preferably use the same frequency band, of bandwidth $2W$. The use of a spreading factor equal to $2N$ is permitted within that bandwidth. The number of users per sector is limited to N (i.e. the total number of
10 users per cell is $4N$) by assigning each user a particular sequence taken from one of the subsets S1 or S2 of N sequences.

The preferred characteristics of the cellular network are therefore as follows:

- 15 - spectral occupancy: $2W$
- spreading factor: $2N$
- number of sequences assigned to a sector: N
- two adjacent sectors use disjoint
subsets of sequences, each of cardinal number: N
- 20 - maximum number of users in each sector: N

It remains to minimize the interference between users of adjoining cells. All the adjoining cells use the same frequency band, the orthogonal relationship is lost because the base transceiver stations are not
25 synchronized, and a user in one cell interferes with all the users in the other cells. The interference is deterministic and non-uniform, however. One way to make it uniform that is known in the art uses additional coding employing different PN sequences in each cell.

30 Each user's signal is therefore first spread by a sequence of length $2N$ and is then multiplied by a sequence PN, also of length $2N$, without additional spectrum spreading. The chips from the Walsh-Hadamard coder are multiplied by the bits of the PN sequence.

35 This latter operation, which is shown in Figure 4, is intended to separate the signals of different cells. There is therefore no interference between users in the

same cell, because their respective codes are orthogonal. However, a given user interferes with users in all the other cells. There is a finite level of interference because the various PN sequences that can be used are not mutually orthogonal.

On the uplink channel from a user terminal to a base transceiver station the base transceiver station receives interference from a small number of users in the fields of their sector whose antennas are oriented towards the base transceiver station at the center of Figure 5, as shown diagrammatically in the shaded areas in Figure 5. The total level of interference is therefore low, and the same for all users.

In contrast to an uplink channel user, a downlink channel user experiences interference which depends on their position within a sector. Consider first the situation of users at the points A, B and C in Figure 6. User A is at the limit of the sector, on a diagonal line passing through the base transceiver station. Their antenna is pointed towards their base transceiver station, which is at a distance $\sqrt{2}D$. The antenna is also directed towards another base transceiver station at a distance $3\sqrt{2}D$. If the sector associated with the other base transceiver station comprises K users, then the C/I ratio is given by the equation:

$$C/I = 10\log[(2N/K)3^2] \quad (1)$$

For a payload signal normalized to 1, the interference created by a single user is $1/2N \times 3^2$, where the terms 3^2 and $2N$ respectively express the ratio of the squares of the distances and the gain due to the PN sequences (the correlation coefficient of two carefully chosen PN sequences of length $2N$ is equal to $1/2N$). In the presence of K users, the C/I ratio is therefore expressed by equation (1). It decreases with K. For $K = N$:

$$C/I = 10\log(2 \times 3^2) = 12.5 \text{ dB}$$

The antenna of the user is also pointed towards other base transceiver stations, also on the diagonal

line, at distances $(2M+1)\sqrt{2}D$, where $M > 1$, but the corresponding interference will not predominate because the distance is greater.

The user B is at the limit of the sector, on the horizontal line passing through the base transceiver station. The user C is also at the limit of the sector, on the vertical line passing through the base transceiver station. Their antenna is pointed towards their base transceiver station, which is at a distance D , and also towards another base transceiver station, at a distance $3 \times D$, and receives interference from two sectors of the cell centered around the other base transceiver station. If the two sectors respectively comprise K_1 and K_2 users, then the C/I ratio is given by the equation:

$$C/I = 10 \log \left[\left(\frac{2N}{K_1 + K_2} \right) \times 3^2 \right]$$

For $K_1 = K_2 = N$, then $C/I = 10 \log(3^2) = 9.5 \text{ dB}$.

Note that these C/I ratios of 12.5 dB and 9.5 dB are valid, within each sector, only in the vicinity of the point A, on the one hand, and in the vicinity of the point B or C, on the other hand. Outside the shaded areas (see Figure 7), the C/I ratio is much greater than the above values.

For example, a receiver at a point A' on the diagonal line half-way between the edge of the sector and the base transceiver station, i.e. at the limit of the shaded area, receives the signal from its base transceiver station much more strongly than an interfering signal from another base transceiver station. If $K = N$ the C/I ratio is then equal to:

$$C/I = 10 \log \left[2 \times \left(\frac{D\sqrt{2}/2 + 2D\sqrt{2}}{D\sqrt{2}/2} \right)^2 \right] = 17 \text{ dB}$$

For the points B' or C' on the horizontal or vertical line halfway between the edge of the sector and

the base transceiver station, i.e. at the limit of the shaded area, if $K = N$ the C/I ratio is equal to:

$$C/I = 10 \log \left[2 \times \left(\frac{D\sqrt{2}/2 + 2D\sqrt{2}}{D\sqrt{2}/2} \right)^2 \right] = 14 \text{ dB}$$

Consequently, in terms of the C/I ratio, it is possible to distinguish three separate areas within a given sector:

- an area of high interference, in the vicinity of the points B and C, where the C/I ratio has a minimum value of 9.5 dB, equal to the value obtained for a system of the same bandwidth $2W$ using the TDMA technique;
- an area of slightly less interference, in the vicinity of the point A, where the C/I ratio can drop to 12.5 dB; and
- finally, the remainder of the sector, where the C/I ratio will always be greater than 14 dB (and even greater than 17 dB between A' and the base transceiver station).

Because the users' antennas are directional, with an aperture angle of the order of 2° to 4° , the area with the lowest C/I ratio will in fact cover the smallest part of the sector, which opens up the possibility of improving the C/I ratios of the areas with lower C/I ratios, subject to a reasonable additional coding cost.

In accordance with the invention, various objectives can be set:

- 1st objective: to improve the C/I ratio of areas B and C (the worst provided for),
- 2nd objective: to improve much more the C/I ratio of areas B and C and in parallel to improve also (but more modestly) the C/I ratio of the area A (which otherwise would become the worst provided for).

The idea of the invention is to assign users at the most unfavorable geographical positions within a sector a coding method enabling them to benefit compared to other

users, in order to compensate their *a priori* handicap. To this effect, the delimitation of the areas A, B and C defined in Figure 5 or 7 merely serves to illustrate this differential treatment according to the user's geographical position. The invention remains perfectly applicable to areas with different limits, for example an area B extending from the point B to a point either beyond or short of the point B' on the horizontal line joining B and the associated base transceiver station.

The C/I ratio is greater than 12.5 dB at all points outside areas B and C. In accordance with the invention, without modifying the duration of the chips, and therefore the spectrum occupancy, a coding sequence of double length $4N$, or triple or quadruple length, instead of a single length $2N$, is associated with downlink calls from a base transceiver station to the disadvantaged users in areas B and C. This reduces by 3 dB for doubling or 4.8 dB for tripling or 6 dB for quadrupling, for these disadvantaged users, the interference caused by a signal transmitted by another adjacent base transceiver station and intended for other users. In practice, Figures 8a and 8b show how each symbol to be transmitted to a disadvantaged user is preferably subjected to at least two successive codings by two single coding sequences of length $2N$ to form a double sequence of length $4N$, and that the coding operation produces symbols comprising $4N$ chips. The sequences of length $4N$ must be orthogonal to the sequences of length $2N$ of other users and must be mutually orthogonal. The bits of these streams of $4N$ successive chips are then processed in a transmitter like the bits of the sequences of $2N$ chips.

The situation is therefore one in which ordinary users employ a single coding sequence of length $2N$ per symbol while disadvantaged users benefit from a double sequence of length $4N$ per symbol. If necessary, a triple or quadruple coding sequence could be allocated for coding the same symbol of messages to be transmitted for

these disadvantaged users. It is just as if redundancy were added by repeating the symbol for only some messages. The messages for which such redundancy is added are messages to users singled out geographically, known to be disadvantaged from the communication point of view, and for whom quality can be improved by singling out the coding sequences assigned to them and doubling (tripling, etc.) the coding of the symbols of their messages by those sequences.

This halves (divides by three, four, etc.) the information bit rate (the duration of the chips remains exactly the same with the same spreading factor, so as not to increase spectrum occupancy), and to compensate for this it is preferable to associate two coding sequences of length $4N$ with the user in question to maintain a constant information bit rate (and therefore to offer that user the same service as other users). The quality improvement of 3 dB is therefore not net, since the number of sequences associated by the base transceiver station will increase.

Assuming that the number of users with double sequences of length $4N$ is equal to m per sector, the total number of single sequences is then $(N-m)+2m = N+m$. $N-m$ users have a single sequence with a coding length of $2N$ and m users have a double sequence with a coding length of $2 \times 2N$. The real improvement in quality is:

$$G = 10 \log (2N / (N+m))$$

$$\text{for } m = N/20 \quad G = 2.8 \text{ dB} \Rightarrow C/I_{(B \text{ or } C)} = 12.3 \text{ dB}$$

$$\text{for } m = N/8 \quad G = 2.5 \text{ dB} \Rightarrow C/I_{(B \text{ or } C)} = 12 \text{ dB}$$

$$\text{for } m = N/4 \quad G = 2.0 \text{ dB} \Rightarrow C/I_{(B \text{ or } C)} = 11.5 \text{ dB}$$

The net gain improves as the number of users requiring a double length sequence is reduced, and therefore as the size of areas B and C is reduced. The invention is perfectly applicable to fixed radio access systems, in which the user terminal antennas are highly directional.

There follows one example of the generation of

elongated sequences from a single length sequence, for
 $N = 4$ and $m = 1$:

1 1 1 11 111	s1	1111111111111111	- 2 sequences
		11111111-1-1-1-1-1-1-1-1	of length $4N=16$
			are associated
			with a user
1-11-11-11-1	s2		- 3 users have
11-1-111-1-1	s3		a sequence of
1-1-111-1-11	s4		length $2N=8$

Figures 8a and 8b show a preferred embodiment of the method according to the invention for a disadvantaged user. The user transmits a message including symbols a_1 , a_2 , a_3 , a_4 , etc. In each symbol time T_s , using conventional CDMA coding, a sequence of length $2N$ would normally be assigned, and in this example $2N$ equals 8. The symbol time T_s is therefore equal to $2N$ times the chip time T_c . In accordance with the invention, the symbol a_1 is assigned a coding sequence of length $4N$ (equal to 16 in this example). The coding sequence naturally last longer than the symbol time T_s of the symbol a_1 , because the number of chips transmitted is doubled without changing the frequency occupancy of the carrier. There are two possible solutions.

Either (Figure 8a) penalizing the user is acceptable and their usable bit rate is halved (or reduced by a factor of three or four, depending on the type of multiple sequence used). In this case, the actual symbol time becomes twice (three times, four times, etc.) the basic symbol time. In practice, to preserve an existing transmitter architecture, the simplest approach is to code a symbol a_1 to be transmitted for a given user twice in succession for each sequence $2N_i$. At the receiver, the simplest approach is to consider a double decoding length $4N$. In this case, the decoder uses a sequence of length $4N$, for example the first sequence indicated above for the user s_1 .

Or (Figure 8b), this penalty is not acceptable, in

which case two coding systems are used and two double coding sequences (each of length $4N$) are used simultaneously. For example, the two double sequences are the two provided above for the user s_1 . Thus, the symbol a_1 is coded by the beginning of its double sequence, by a first subsystem. Then coding of the symbol a_2 is begun by a second subsystem using the beginning of its double sequence, while the symbol a_1 is still being coded by the first subsystem using the second part of its double sequence. Each double sequence has a length $4N$ and a duration $4N$ times T_c . When the first subsystem has completed generating the chips relating to the symbol a_1 , it immediately begins to generate the chips relating to the symbol a_3 , under the same conditions, although the symbol a_2 is still being coded by the second subsystem. And so on. If coding sequences of triple or quadruple length are chosen, three or four coding subsystems preferably operate simultaneously. Clearly by adopting this approach at least two symbols are transmitted simultaneously, at least in part. In this case, an appropriate receiver would have to include two (three, four) decoder subsystems, used simultaneously to decode alternately symbols a_1 , a_2 , a_3 , a_4 of a message transmitted to that user.

The first double sequence includes a repetition of the same single sequence (here with eight 1s) and the second double sequence includes a single sequence (the same as for the first double sequence) and another single sequence complementary to the first single sequence. In this way the two double sequences are orthogonal to each other. In theory, it would be possible to constitute the double sequences from any single sequence, provided that the double sequences obtained were mutually orthogonal. However, because the double sequences are made up of single sequences, mutually orthogonal single sequences whose number is limited (to $2N$), and therefore limits the number of users in the cell, must not be neutralized

unnecessarily.

Note that doubling, tripling or otherwise multiplying the subsystems is not a particularly high penalty in terms of hardware because coding and decoding are handled by processors already incorporated in the base transceiver station and the user terminals.

In Figure 8b, the symbols a_1 and a_2 could also be transmitted simultaneously on the two subsystems, followed by transmission of the symbols a_3 and a_4 , and so on.

To achieve greater improvement, by allocating users in high interference areas even longer sequences, for example sequences of length $8N$, and in order to comply with the constraint that the spectrum occupancy must not be increased, the number of sequences to be allocated to those users is also greater (4 for sequences of length $8N$). The following strategy could be used, for example:

- use sequences of length $8N$ for users in areas B and C: the gross improvement is 6 dB;

- use sequences of length $4N$ for users in area A: the gross improvement is 3 dB.

The following example illustrates this allocation:

- Total number of users: $N = 4$
- Number of users in area B or C: $m_1 = 1$
- Number of users in area A: $m_2 = 1$

Consider a user in area B or C with four sequences of length $8N$ generated from the sequence 11111111, which becomes, on the one hand:

11111111 11111111,

which becomes:

11111111 11111111 11111111 11111111, and

11111111 11111111 -1-1-1-1-1-1-1-1 -1-1-1-1-1-1-1-1,

and, on the other hand:

11111111 -1-1-1-1-1-1-1-1

which becomes:

11111111 -1-1-1-1-1-1-1-1 11111111 -1-1-1-1-1-1-1-1, and

11111111 -1-1-1-1-1-1-1-1 -1-1-1-1-1-1-1-1 11111111.

It can be seen that again a single sequence is used to produce all of the quadruple sequences. The single sequence is only combined with its complementary image. Thus a single sequence is preferably concatenated with one repetition of that single sequence or with a complementary single sequence.

Consider a user in area A with two sequences of length $4N$ generated from the sequence 1-11-11-11-1 which becomes, on the one hand:

1-11-11-11-1 1-11-11-11-1

and, on the other hand:

1-11-11-11-1 -11-11-11-11.

Consider two users with a sequence of length $2N$:

(a) 11-1-111-1-1, and

(b) 1-1-111-1-11.

For the general case, the net improvement can be evaluated by considering the total number of users (N), the number of users in area B or C (m_1) and the number of users in area A (m_2):

$$\begin{aligned} \text{Total number of sequences: } T &= (N - m_1 - m_2) + 4 \times m_1 + 2 \times m_2 \\ &= N + 3 \times m_1 + 1 \times m_2 \end{aligned}$$

In area B or C, the net improvement is therefore:

$$G_{\text{net}} = 10 \log \left(4 \times \frac{N}{N + 3m_1 + m_2} \right)$$

In the above equation:

(i) the factor 4 expresses the lengthening by a factor 4 of the sequences assigned to users in area B or area C;

(ii) the factor $N/(N + 3m_1 + m_2)$ expresses the ratio between the total number of single sequences assigned, allowing for the assigning of several single sequences to users in certain areas, and the number of single sequences that would be assigned if all users had only one sequence.

In area A, the net improvement is

$$G_{\text{net}} = 10 \log \left(2 \times \frac{N}{N + 3m_1 + m_2} \right)$$

In the above equation:

(i) the factor 2 expresses the lengthening by a factor 2 of the single sequences assigned to users in area A;

5 (ii) the factor $N/(N+3m_1+m_2)$: see above.

This leads to the following numerical examples:

(a) $m_1 = N/8$ and $m_2 = N/8$

For area B or C, the C/I ratio with no lengthening of the sequences is 9.5 dB, the gross improvement due to
10 lengthening the sequences is 6 dB, and the reduction of the improvement due to the increase in the number of sequences is 1.8 dB. The minimum C/I ratio in area B or C is 13.7 dB.

For area A, the C/I ratio in the absence of
15 lengthening of the sequence is 12.5 dB, the gross improvement due to lengthening the sequences is 3 dB, and the reduction of the improvement due to the increase in the number of sequences is 1.8 dB. The minimum C/I ratio in area A is therefore 13.7 dB.

20 (b) $m_1 = N/20$ and $m_2 = N/20$

For area B or C, the C/I ratio with no lengthening of the sequences is 9.5 dB, the gross improvement due to lengthening the sequences is 6 dB, and the reduction of the improvement due to the increase in the number of
25 sequences is 0.8 dB. The minimum C/I ratio in area B or C is 14.7 dB.

For area A, the C/I ratio in the absence of
lengthening of the sequences is 12.5 dB, the gross improvement due to lengthening the sequences is 3 dB, and
30 the reduction of the improvement due to the increase in the number of sequences is 0.8 dB. The minimum C/I ratio in area A is therefore 14.7 dB.

The ratios m/N can be evaluated by calculating the ratio between the areas of the shaded portions of a
35 sector and of the sector itself (assuming that the user terminals are uniformly distributed within a sector). This ratio depends on the directionality of the users'

antennas. If users are distributed homogeneously within a sector, example (b) corresponds to the situation in which the combination (area B + area C) covers 5% of the area of a sector, the area A also covers 5% and the "unshaded" area covers 90%.

The above considerations have been developed in the context of an ideal rectangular cellular network. They could equally be applied to other cellular network topologies, for example ones using a hexagonal pattern, in which the base transceiver stations use 120° sectorial antennas. In a real system, installed in the field, the geometry of the cells is not as regular, as it must take into account the topography of the terrain and the existence of buildings.

Interference can in some cases be partly reduced by carefully choosing the location and the height of the base transceiver stations, within the limits of the possibilities offered by the terrain and buildings.

In contrast, the user terminals are in practice too numerous to benefit from these engineering techniques. Also, their installation site is fundamentally determined by the residence of the user, and not by engineering parameters. Unlike the base transceiver stations, their installation cannot call on teams with expertise in site engineering techniques.

It is impossible in practice to minimize interference in a really significant manner by using conventional engineering techniques.

Consequently, the method described above is of great benefit: it is very simple to use in a fixed service system, because it is sufficient to allocate the lengthened sequences to the user stations whose geographical location corresponds to the high interference areas. It is also possible, by deducing an interference map from the nature of the terrain and buildings, to predict the level of interference that a user at a given location will experience and therefore to

5

device associated with the stations, for example.

10

CLAIMS

1. A method of transmitting CDMA messages between a base transceiver station and user terminals, wherein:

- symbols of messages to certain user terminals are coded with a coding sequence of $2N$ bits to produce sequences of $2N$ chips, and

- the chips are transmitted, characterized in that:

- symbols of other messages to certain other user terminals are coded with a coding sequence of $k2N$ bits to produce sequences of $k2N$ chips, where k is an integer greater than 1.

2. A method according to claim 1, characterized in that at least two symbols of said other messages are transmitted simultaneously.

3. A method according to claim 2, characterized in that k symbols of said other messages are transmitted simultaneously.

4. A method according to any one of claims 1 to 3, characterized in that:

- a radiation cell of a base transceiver station is divided into sectors,

- a common carrier frequency is used for all the sectors of the cell,

- coding sequences are divided into subsets (S_1 , S_2), and

- different subsets are assigned to user terminals which are located in adjoining or contiguous sectors.

5. A method according to any one of claims 1 to 4, characterized in that different base transceiver stations of a cellular system transmit chips on a common carrier frequency and with a common pass-band.

6. A method according to any one of claims 1 to 5, characterized in that the symbols or the chips are coded by random bit sequences (PN).

5 7. A method according to any one of claims 1 to 6, characterized in that a single sequence is concatenated with a repetition of that single sequence or with a complementary single sequence to constitute a coding sequence $k2N$.

10 8. A method according to any one of claims 1 to 7, characterized in that decoding subsystems are used simultaneously in a user terminal k to decode in parallel k symbols of a message transmitted to that user.

15 9. A method according to any one of claims 1 to 8, characterized in that a symbol is decoded in a user terminal with a decoding sequence of length $k2N$.

A B S T R A C T

A METHOD OF REDUCING INTERFERENCE BETWEEN USERS AND USE
OF THE METHOD IN A RADIO ACCESS NETWORK

In a network of fixed radio links, base transceiver stations radiate omnidirectionally or sectorially. User terminals are provided with directional antennas oriented towards the base transceiver stations. The CDMA mode is one mode of coding symbols to be transmitted before modulation by a carrier. Some user terminals are situated in disadvantaged areas of the network, where they receive unwanted transmissions from other base transceiver stations aligned with their pointing direction. To prevent the harmful effects of such unwanted transmissions, the signals intended for those user terminals are coded with double length coding sequences. It is shown that this redundancy improves transmission quality by up to 3 dB. Quality is further improved by further increasing the length of the sequences.

Translation of the title and the abstract as they were when originally filed by the Applicant. No account has been taken of any changes that may have been made subsequently by the PCT Authorities acting ex officio, e.g. under PCT Rules 37.2, 38.2, and/or 48.3.




Fig. 1




Fig. 2




Fig. 3





Fig. 5




Fig. 6




Fig. 7




Fig. 8a




Fig. 8b

French Language Declaration

Declaration and Power of Attorney for Patent Application

Déclaration et Pouvoirs pour Demande de Brevet

French Language Declaration

En tant que l'inventeur nommé ci-après, je déclare par le présent acte que:

As a below named inventor, I hereby declare that

Mon domicile, mon adresse postale et ma nationalité sont ceux figurant ci-dessous à côté de mon nom.

My residence, post office address and citizenship are as stated next to my name.

Je crois être le premier inventeur original et unique (si un seul nom est mentionné ci-dessous), ou l'un des premiers co-inventeurs originaux (si plusieurs noms sont mentionnés ci-dessous) de l'objet revendiqué, pour lequel une demande de brevet a été déposée concernant l'invention de la description identifiée par le numéro de référence

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention in the specification identified by Docket No.

111391/LA/RCD

Je déclare par le présent acte avoir passé en revue et compris le contenu de la description ci-dessus, revendications comprises.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims.

Je reconnais devoir divulguer toute information pertinente à la brevetabilité, comme défini dans le Titre 37, § 1.56 du Code fédéral des réglementations.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

Je revendique par le présent acte avoir la priorité étrangère, en vertu du Titre 35, § 119(a)-(d) ou § 365(b) du Code des Etats-Unis, sur toute demande étrangère de brevet ou certificat d'inventeur ou, en vertu du Titre 35, § 365(a) du même Code, sur toute demande internationale PCT désignant au moins un pays autre que les Etats-Unis et figurant ci-dessous et, j'ai aussi indiqué ci-dessous toute demande étrangère de brevet, tout certificat d'inventeur ou toute demande internationale PCT ayant une date de dépôt précédant celle de la demande à propos de laquelle une priorité est revendiquée.

I hereby claim foreign priority under Title 35, United States Code, § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below, and have also identified below any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed

Prior foreign application(s) for which priority is claimed

Demande(s) de brevet étrangère(s) antérieure(s) dont la priorité est revendiquée

(Number) (Numéro)	(Country) (Pays)	(Day/Month/Year Filed) (Jour/Mois/Année de dépôt)
9904754	FRANCE	15 APRIL 1999

Prior foreign applications for which priority is not claimed

Demande(s) de brevet étrangères antérieure(s) dont la priorité n'est pas revendiquée

(Number) (Numéro)	(Country) (Pays)	(Day/Month/Year Filed) (Jour/Mois/Année de dépôt)

French Language Declaration

Je revendique par le présent acte tout bénéfice, en vertu du Titre 35, § 119(e) du Code des Etats-Unis, de toute demande de brevet provisoire effectuée aux Etats-Unis et figurant ci-dessous.

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below.

(Application No.)
(No de demande)

(Filing Date)
(Date de dépôt)

Je revendique par le présent acte tout bénéfice, en vertu du Titre 35, § 120 du Code des Etats-Unis, de toute demande de brevet effectuée aux Etats-Unis, ou en vertu du Titre 35, § 365(c) du même Code, de toute demande internationale PCT désignant les Etats-Unis et figurant ci-dessous et, dans la mesure où l'objet de chacune des revendications de cette demande de brevet n'est pas divulgué dans la demande antérieure américaine ou internationale PCT, en vertu des dispositions du premier paragraphe du Titre 35, § 112 du Code des Etats-Unis, je reconnais devoir divulguer toute information pertinente à la brevetabilité, comme défini dans le Titre 37, § 1.56 du Code fédéral des réglementations, dont j'ai pu disposer entre la date de dépôt de la demande antérieure et la date de dépôt de la demande nationale ou internationale PCT de la présente demande.

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Application No.)
(N0 de demande)

(Filing Date)
(Date de dépôt)

(Status)(patented, pending, abandoned)
(Statut)(breveté, en cours d'examen, abandonné)

Je déclare par le présent acte que toute déclaration ci-incluse est, à ma connaissance, véridique et que toute déclaration formulée à partir de renseignements ou de suppositions est tenue pour véridique; et de plus, que toutes ces déclarations ont été formulées en sachant que toute fausse déclaration volontaire ou soit équivalent est passible d'une amende ou d'une incarcération, ou des deux, en vertu de la Section 1001 du Titre 18 du Code des Etats-Unis, et que de telles déclarations volontairement fausses risquent de compromettre la validité de la demande de brevet ou du brevet délivré à partir de celle-ci.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

French Language Declaration

POUVOIRS: En tant que l'inventeur cité, je désigne par la présente l'(les) avocat(s) et/ou agent(s) suivant(s) pour qu'ils poursuive(nt) la procédure de cette demande de brevet et traite(nt) toute affaire s'y rapportant avec l'Office des brevets et des marques: (mentionner le nom et le numéro d'enregistrement).

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: (list name and registration number)

John H. Mion, Reg. No. 18,879; Thomas J. Macpeak, Reg. No. 19,292; Robert J. Seas, Jr., Reg. No. 21,092; Darryl Mexic, Reg. No. 23,063; Robert V. Sloan, Reg. No. 22,775; Peter D. Olexy, Reg. No. 24,513; J. Frank Osha, Reg. No. 24,625; Waddell A. Biggart, Reg. No. 24,861; Louis Gubinsky, Reg. No. 24,835; Neil B. Siegel, Reg. No. 25,200; David J. Cushing, Reg. No. 28,703; John R. Inge, Reg. No. 26,916; Joseph J. Ruch, Jr., Reg. No. 26,577; Sheldon I. Landsman, Reg. No. 25,430; Richard C. Turner, Reg. No. 29,710; Howard L. Bernstein, Reg. No. 25,665; Alan J. Kasper, Reg. No. 25,426; Kenneth J. Burchfiel, Reg. No. 31,333; Gordon Kit, Reg. No. 30,764; Susan J. Mack, Reg. No. 30,951; Frank L. Bernstein, Reg. No. 31,484; Mark Boland, Reg. No. 32,197; William H. Mandir, Reg. No. 32,156; Scott M. Daniels, Reg. No. 32,562; Brian W. Hannon, Reg. No. 32,778; Abraham J. Rosner, Reg. No. 33,276; Bruce E. Kramer, Reg. No. 33,725; Paul F. Neils, Reg. No. 33,102; and Brett S. Sylvester, Reg. No. 32,765; and Robert M. Masters, Reg. No. 35,603.

Adresser toute correspondance à

Send Correspondence to:

SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC
2100 Pennsylvania Avenue, N.W., Suite 800
Washington, D.C. 20037-3213

Nom complet de l'unique ou premier inventeur		Full name of sole or first inventor (First Middle Last)	
Signature de l'inventeur		Inventor's signature	
Date		Date	
Domicile		Residence	
Nationalité		Citizenship	
Adresse postale		Post Office Address	
Nom complet du second co-inventeur, le cas échéant		Full name of second joint inventor, if any (First Middle Last)	
Signature du second inventeur		Second inventor's signature	
Date		Date	
Domicile		Residence	
Nationalité		Citizenship	
Adresse postale		Post Office Address	

(Fournir les mêmes renseignements et la signature de tout co-inventeur supplémentaire.)

(Supply similar information and signature for third and subsequent joint inventors.)